

CONVENIENT • EFFICIENT • ECO-FRIENDLY

PureFlo® Bright

Carbon Filtration Solution



PureFlo® Bright is an advanced filtration solution using proven carbon filters, built-in IoT (Internet of Things) enabled smart monitoring technology, easy installation and convenient features. With PureFlo Bright filtration in your home or business, you can be sure your employees, guests and family enjoy pure, high-quality, great-tasting water at the touch of a button.

Carbon filtration benefits

- Removes chlorine, chloramine, chemicals, pharmaceuticals, taste and odor
- Leaves minerals in the water

Carbon Shaker™ filtration technology

- High-quality filter media attached to the cooler compressor
- Compressor vibrates the filter and media multiple times per hour, creating new pathways for water
- Extends filter quality, longevity and effectiveness over traditional carbon filters
- Longer filter life helps lessen environmental impact

Built-in smart technology

- IoT monitoring detects leaks and measures water throughput
- Water leaks trigger automatic shutoff and an automated service call
- QR code links to dashboard for system visibility and validation

Antimicrobial surface treatment

- Water dispenser levers are treated with an antimicrobial surface treatment
- Silver ion technology inhibits bacterial growth on high-touch surfaces

Convenient professional installation

- Hard-plumbed
- Does not require a drain connection

Certification and testing

- Meets [NSF/ANSI 42, 401, 372 & CSA B483.1](#) filtration system standards for drinking water
- Accredited, third-party certification by the Water Quality Association (WQA) Gold Seal certification program
- Extensive testing to evaluate product structural integrity, ability to reduce contaminants and safety of materials that contact water

PUREFLO®

CONVENIENT • EFFICIENT • ECO-FRIENDLY

PureFlo® Bright

Carbon Filtration Solution



Technical Specifications

Product Height: 44.4"

Product Width: 12.6"

Product Depth: 13.4"

Product Weight: 43 lbs.

Power Rating: 110-115V; 60Hz

Consumption Power: 500W heating; 70W cooling

Cold Water Temperature Range: 4°C - 10°C, 39.2°F - 50°F

Cold Water Tank Capacity: About 1.5 L/54 oz./.42 gal

Hot Water Temperature Range: 76°C - 92°C,
168.8°F - 197.6°F

Hot Water Tank Capacity: About 1.1 L/38.4 oz./.3 gal

Recommended Number of Users: 1-20*

*Data is based on recommended eight 8-ounce glasses a day

Child Safety

Child safety lock on the hot water spout
to help prevent accidents

PUREFLO®

